

# Q25

## UPGRADED Smart PINpad



Supermarkets



Fashion & Retail



Food & Beverage



**CLASSIC**



Powered by  
Prolin



PCI 5  
SRED



2.8"  
Display





















0.3MP  
Front



Pole Stand  
Option

## SPECIFICATIONS

	<b>Operating System</b>	Prolin
	<b>Processor</b>	Cortex A7
	<b>Memory</b>	256MB FLASH + 256MB DDR RAM
	<b>Card Readers</b>	Chip & PIN   NFC Contactless   Magnetic Stripe
	<b>Cameras</b>	0.3MP Front-Facing (optional)
	<b>Display</b>	2.8" TFT QVGA 320 x 240 Pixels Touch Screen (optional)
	<b>Comms Configurations</b>	RS232   Fast Ethernet   USB 2.0   Wi-Fi® 2.4GHz/5GHz (optional)
	<b>Battery</b>	No
	<b>Printer</b>	No
	<b>SIM / SAM</b>	2 Micro PSAM, 3rd Optional
	<b>Positioning</b>	No
	<b>Keys / Buttons</b>	18 Keys: Menu   Up   Down   Func   0~9   Alpha   Enter   Clear   Cancel   Back-Lighting (optional)
	<b>Audio</b>	1 Speaker   Audio Jack (optional)
	<b>Ports</b>	Multi-Functional Port   1 Type-C USB 2.0, OTG (optional)   1 Kensington
	<b>Physical</b>	159 x 80 x 43mm, 260g
	<b>Environmental</b>	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 93% Relative Humidity, Non-Condensing
	<b>Power Supply</b>	Input: 100 ~ 240V AC, 50Hz/60Hz Output: 5.0V DC, 1.0A
	<b>Accessories</b>	Privacy Shields   Multiple Cabling Options
	<b>Certifications</b>	PCI PTS 5.x, SRED   EMV L1 & L2   EMV Contactless L1   Mastercard contactless Visa payWave   American Expresspay   Discover D-PAS   Interac Flash J/Speedy   qUICS   Mastercard TQM   UL   CE   FCC   IC   RoHS

