

Q30

CHIC

Smart PINpad



Supermarkets



Fashion & Retail



Food & Beverage



CLASSIC



Powered by
Prolin



PCI 5
SRED



4"
Display



0.3MP
Front



















Pole Stand
Option

Q30

Linux
Smart PINpad

SPECIFICATIONS

	Operating System	Prolin
	Processor	Cortex A9
	Memory	512MB FLASH + 512MB DDR RAM Extended microSD Card Slot Up to 32GB
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Cameras	Optional 0.3MP Front-Facing
	Display	4" TFT WVGA 800 x 480 Pixels Touch Screen Electronic Signature Capture
	Comms Configurations	RS232 Fast Ethernet USB 2.0 Wi-Fi® 2.4GHz/5GHz (optional) Bluetooth® (optional)
	SIM / SAM	3 PSAM Card Reader 2 SIM Card Slot Maximum
	Keys / Buttons	13 Keys: 0-9 Enter Cancel Clear Back-Lighting Reset Button
	Audio	1 Buzzer (1 speaker optional)
	Ports	Single Multi-Port Connector 1 RS232 1 USB2.0 OTG 1 Ethernet
	Physical	199 x 112 x 53mm, 400g
	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 93% Relative Humidity, Non-Condensing
	Power Supply	Input: 100 ~ 240V AC, 50Hz / 60Hz Output: 5.0V DC, 1.0A
	Accessories	PS200 Pole Stand Privacy Shields Multiple Cabling Options
	Certifications	PCI PTS 5.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless UPI qUICS Amex Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs

